

## Recessed Parabolic Louvre Fluorescent Fittings

This is a high efficiency recessed luminaire. The high efficiency parabolic reflector provides a batwing light distribution and permits extended spacing between luminaires without loss of uniformity. The reflector is hinged to the housing allowing easy maintenance.



**Model : KSC/AR 320**

### Technical Data

Light Source	: Fluorescent lamp 3 x 18W ( 240V 50Hz )
Construction	: In heavy gauge steel sheet and fully pre-treated.
Louvre	: High quality pure silver finish. Parabolic shaped vanes ensure high efficiency optimal light output with wide distribution and good uniformity.
Mechanical Mounting	: T - Bar suspended ceiling. ( Recessed Type )
Hole Opening Dimension	: 595mm W x 595mm L ( Metric ) or 603mm W x 603mm L ( Imperial)
Expose Frame Dimension	: 595mm W ( Metric ) or 603mm W ( Imperial ) x 613mm L x 93mm Ht.
Paintwork	: High grade white polyester powder coated high reflectance finish.
Ballast	: 6W extra low loss ballast.
Optional Components	: High frequency electronic ballast. ( EB ) : Top mirror. ( TM ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )
Applications	: Offices, Department stores, Reception areas, Halls, Showroom and Libraries.

### Ordering Code

**Example : KSC/AR320 / 2' X 2' / TM / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@gmail.com

D 2  
Rev. A