

Recessed Parabolic Louvre Fluorescent Fittings

This is a high efficiency recessed luminaire. The high efficiency parabolic reflector provides a batwing light distribution and permits extended spacing between luminaires without loss of uniformity. The reflector is hinged to the housing allowing easy maintenance.



Model : KSC/AR 420

Technical Data

Light Source	: Fluorescent lamp 4 x 18W (240V 50Hz)
Construction	: In heavy gauge steel sheet and fully pre-treated.
Louvre	: High quality pure silver finish. Parabolic shaped vanes ensure high efficiency optimal light output with wide distribution and good uniformity.
Mechanical Mounting	: T - Bar suspended ceiling. (Recessed Type)
Hole Opening Dimension	: 595mm W x 595mm L (Metric) or 603mm W x 603mm L (Imperial)
Expose Frame Dimension	: 595mm W (Metric) or 603mm W (Imperial) x 613mm L x 93mm Ht.
Paintwork	: High grade white polyester powder coated high reflectance finish.
Ballast	: 6W extra low loss ballast.
Optional Components	: High frequency electronic ballast. (EB) : Top mirror. (TM) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)
Applications	: Offices, Department stores, Reception areas, Halls, Showroom and Libraries.

Ordering Code

Example : KSC/AR420 / 2' X 2' / TM / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@gmail.com

D 3
Rev. A