

## Parabolic Louvre Fluorescent Fittings With Air Handling

This is a high efficiency recessed luminaire. The high efficiency parabolic reflector provides a batwing light distribution and permits extended spacing between luminaires without loss of uniformity. The reflector is hinged to the housing allowing easy maintenance. The luminaire can be supplied with two air slots along of the luminaire which can be used for air-handling purposes.

**Model : KSC/AR 320 / AH**

### Technical Data

Light Source	: Fluorescent lamp 3 x 18W ( 240V 50Hz )	
Construction	: In heavy gauge steel sheet and fully pre-treated.	
Louvre	: High quality pure silver finish. Parabolic shaped vanes ensure high efficiency optimal light output with wide distribution and good uniformity.	
Mechanical Mounting	: T - Bar suspended ceiling. ( Recessed Type )	
Hole Opening Dimension	: 595mm W x 595mm L ( Metric ) or 603mm W x 603mm L ( Imperial)	
Expose Frame Dimension	: 595mm W ( Metric ) or 603mm W ( Imperial ) x 613mm L x 93mm Ht.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast.	( EB )
	: Top mirror.	( TM )
	: EL emergency power pack.	( EL )
	: 2 amp Fused terminal block.	( FTB )
	: Radio interference suppressors.	( RIS )
Applications	: Offices, Department stores, Reception areas, Halls, Showroom and Libraries.	

### Ordering Code

**Example : KSC/AR320 / AH / 2' X 2' / TM / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@gmail.com

