

## Suspended Ceiling Fluorescent Fittings

This fully recessed luminaire is designed for exposed Tee-Bar suspended ceiling with a wide range of diffuser to suit individuals taste and preferences.



**Model : KSC 220**

### Technical Data

Light Source	: Fluorescent lamp 18W ( 240V 50Hz )
Construction	: In heavy gauge steel sheet and fully pre-treated.
Mechanical Mounting	: T - Bar suspended ceiling. ( Recessed Type )
Dimension	: KSC220 2 x 18W = 298mmW ( Imperial ) or 295mmW ( Metric ) x 613mmL x 105mmHt. : KSC220 2 x 18W = 603mmW ( Imperial ) or 595mmW ( Metric ) x 613mmL x 105mmHt. : KSC320 3 x 18W = 603mmW ( Imperial ) or 595mmW ( Metric ) x 613mmL x 105mmHt. : KSC420 4 x 18W = 603mmW ( Imperial ) or 595mmW ( Metric ) x 613mmL x 105mmHt.
Paintwork	: High grade white polyester powder coated high reflectance finish.
Diffuser	: PS12 Polystyrene. ( PS12 )
Ballast	: 6W extra low loss.
Optional Components	: M12 Acrylic diffuser. ( M12 ) : Opal. ( O ) : Parabol louvre. ( P L ) : High frequency electronic ballast. ( EB ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )
Applications	: Offices, Libraries and Department stores.

### Ordering Code

**Example : KSC220 / 2' X 2' / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@gmail.com