

Fluorescent Fittings With Internal Metal Reflector

This recessed luminaire has been specially designed to produce a symmetrical downward light distribution.



Model : KSC/IMR 240

Technical Data

Light Source	: Fluorescent lamp 18W or 36W (240V 50Hz)
Construction	: In heavy gauge steel sheet and fully pre-treated.
Mechanical Mounting	: T - Bar suspended ceiling. (Recessed Type)
Dimension	: KSC/IMR220 2 x 18W =603mmW (Imperial) or 595mmW (Metric) x 613mmL x 96mmHt. : KSC/IMR320 3 x 18W =603mmW (Imperial) or 595mmW (Metric) x 613mmL x 96mmHt. : KSC/IMR240 2 x 36W =603mmW (Imperial) or 595mmW (Metric) x 1,223mmL x 96mmHt. : KSC/IMR340 3 x 36W =603mmW (Imperial) or 595mmW (Metric) x 1,223mmL x 96mmHt.
Paintwork	: High grade white polyester powder coated high reflectance finish.
Optional Components	: High frequency electronic ballast. (EB) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)
Applications	: Electronic factories and Assembly lines.

Ordering Code

Example : KSC/IMR240 / 2' X 4' / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Batu 6 1/2, Jalan Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-5751662 Fax : 603-5753006 Email : kslite@gmail.com