

## Recessed Hinged Diffuser Fluorescent Fittings

This recessed luminaire is designed for exposed Tee-Bar suspended ceiling with hinged diffuser for easy maintenance. The diffuser is framed in steel with spring loaded hinged and latches. The luminaire can also be supplied with two air slots along both sides of the luminaire which can be used for air-handling purposes.



**Model : KSC/HD/AH 240**

### Technical Data

Light Source	: Fluorescent lamp 18W or 36W ( 240V 50Hz )
Construction	: In heavy gauge steel sheet and fully pre-treated.
Mechanical Mounting	: T - Bar suspended ceiling. ( Recessed Type )
Dimension	: 2' x 2' = 603mmW ( Imperial ) or 595mmW ( Metric ) x 613mmL x 105mmHt. : 2' x 4' = 603mmW ( Imperial ) or 595mmW ( Metric ) x 1,223mmL x 105mmHt.
Paintwork	: High grade white polyester powder coated high reflectance finish.
Diffuser	: PS12 Polystyrene. ( PS12 )
Ballast	: 6W extra low loss.
Optional Components	: M12 Acrylic diffuser. ( M12 ) : Opal. ( O ) : Parabol louvre. ( P L ) : High frequency electronic ballast. ( EB ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )
Applications	: Offices, Libraries, Halls, Hospital and Offices.

### Ordering Code

**Example : KSC/HD/AH240 / 2' X 4' / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@gmail.com