

Surfaced Mounted Fluorescent Fittings

This elegant surface mounted luminaire is designed for use in interiors and administrative offices where a high degree of downward lighting is required with minimum glare.



Model : KM 240 (1' x 4')

Technical Data

Light Source	: Fluorescent lamp 36W (240V 50Hz)
Construction	: In heavy gauge steel sheet and fully pre-treated.
Mechanical Mounting	: Surfaced mounted.
Dimension	: KM240 2 x 36W = 305mmW x 1,223mmL x 83mmHt. : KM240 2 x 36W = 610mmW x 1,223mmL x 83mmHt. : KM340 3 x 36W = 610mmW x 1,223mmL x 83mmHt. : KM440 4 x 36W = 610mmW x 1,223mmL x 83mmHt.
Paintwork	: High grade white polyester powder coated high reflectance finish.
Diffuser	: PS12 Polystyrene. (PS12)
Ballast	: 6W extra low loss.
Optional Components	: M12 Acrylic diffuser. (M12) : Opal. (O) : Parabol louvre. (P) : High frequency electronic ballast. (EB) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)
Applications	: Staircase, Corridor and Stores.

Ordering Code

Example : KM240 / 1' X 4' / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@gmail.com