

Modular Recessed Fluorescent Fittings

This quality recessed luminaire is design to suit almost any ceiling. The flushed-looking provides strong appeal as well as good illumination for visual comfort.



Model : KMR 240

Technical Data

Light Source	: Fluorescent lamp 36W (240V 50Hz)
Construction	: In heavy gauge steel sheet and fully pre-treated.
Mechanical Mounting	: Wood ceiling or plaster ceiling. (Opening Dimension)
Dimension	: KMR240 2 x 36W = 330mmW x 1,248mmL x 83mmHt. (308mmW x 1,225mm L) : KMR240 2 x 36W = 636mmW x 1,248mmL x 83mmHt. (612mmW x 1,225mm L) : KMR340 3 x 36W = 636mmW x 1,248mmL x 83mmHt. (612mmW x 1,225mm L) : KMR440 4 x 36W = 636mmW x 1,248mmL x 83mmHt. (612mmW x 1,225mm L)
Paintwork	: High grade white polyester powder coated high reflectance finish.
Diffuser	: PS12 Polystyrene. (PS12)
Ballast	: 6W extra low loss.
Optional Components	: M12 Acrylic diffuser. (M12) : Opal. (O) : Parabol louvre. (PL) : High frequency electronic ballast. (EB) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)
Applications	: Offices, Libraries and Department stores.

Ordering Code

Example : KMR340 / 2' X 4' / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@gmail.com