

Bare Channel Fluorescent Fittings

This is a high quality basic channel fitting with an unshielded fluorescent tube. Recommended for economical general purpose light. Suitable for ceiling mounting, wall mounting or pendent mounted by suspension rods.

**Model : KB 340****Model : KB 240****Model : KB 140**

Technical Data

Light Source	: Fluorescent lamp 18W or 36W (240V 50Hz)	
Construction	: In heavy gauge steel sheet and fully pre-treated.	
Mechanical Mounting	: Surface or wall mounted.	
Dimension	: KB120 1 x 18W = 56mmW x 610mmL x 80mmHt.	
	: KB220 2 x 18W = 138mmW x 610mmL x 90mmHt.	
	: KB140 1 x 36W = 56mmW x 1,220mmL x 80mmHt.	
	: KB240 2 x 36W = 138mmW x 1,220mmL x 90mmHt.	
	: KB340 3 x 36W = 150mmW x 1,220mmL x 90mmHt.	
Paintwork	: High grade white polyester powder coated high reflectance finish.	
Ballast	: 6W extra low loss ballast.	
Optional Components	: High frequency electronic ballast.	(EB)
	: EL emergency power pack.	(EL)
	: 2 amp Fused terminal block.	(FTB)
	: Radio interference suppressors.	(RIS)
Applications	: Storage plants, Factories, Garages, Car park & corridors.	

Ordering Code

Example : KB 140 / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@gmail.com

J 1
Rev. A