

Bare Channel Wire-Guard Fluorescent Fittings

This luminaire is designed for use in areas where security of the tube are necessary. The wire guard is hinged on one side of the casing.



Model : KWG 140 / KWG 240

Technical Data

Light Source	: Fluorescent lamp 18W or 36W (240V 50Hz)
Construction	: In heavy gauge steel sheet and fully pre-treated.
Mechanical Mounting	: Surface or wall mounted.
Dimension	: KWG120 1 x 18W = 105mmW x 610mmL x 110mmHt. : KWG220 2 x 18W = 155mmW x 610mmL x 115mmHt. : KWG140 1 x 36W = 105mmW x 1,220mmL x 110mmHt. : KWG240 2 x 36W = 155mmW x 1,220mmL x 115mmHt.
Paintwork	: High grade white polyester powder coated high reflectance finish.
Ballast	: 6W extra low loss ballast.
Optional Components	: High frequency electronic ballast. (EB) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)
Applications	: Car park & similar location where vandalism and breakage occurs quite frequently.

Ordering Code

Example : KWG 140 / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@gmail.com

K 1
Rev. B