

Channel Diakon Diffuser Fluorescent Fittings

This surface mounted luminaire is designed to meet the performance of visual comfort and appearance.



Model : KD240 and KD140

Technical Data

Light Source	: Fluorescent lamp 18W or 36W (240V 50Hz)
Construction	: In heavy gauge steel sheet and fully pre-treated.
Mechanical Mounting	: Surface or wall mounted.
Dimension	: KD120 1 x 18W = 63mmW x 610mmL x 93mmHt. : KD220 2 x 18W = 128mmW x 610mmL x 103mmHt. : KD140 1 x 36W = 63mmW x 1,220mmL x 93mmHt. : KD240 2 x 36W = 128mmW x 1,220mmL x 103mmHt. : KD120 1 x 18W = 68mmW x 610mmL x 113mmHt. (Round diffuser) : KD140 1 x 36W = 68mmW x 1,220mmL x 113mmHt. (Round diffuser)
Paintwork	: High grade white polyester powder coated high reflectance finish.
Diffuser	: PS10 Polystyrene diffuser.
Ballast	: 6W extra low loss ballast.
Optional Components	: Opal diffuser. (O) : M12 acrylic diffuser. (M12) : High frequency electronic ballast. (EB) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)
Applications	: Staircase areas, Toilets and Corridors.

Ordering Code

Example : KD 140 / EL / FTB / RIS

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Batu 6 1/2, Jalan Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-5751662 (H/L) Fax : 603-5753006 Email : kslite@gmail.com