

## Triangle Shaped Fluorescent Fittings

This luminaire is a modern version of the batten fitting. The arrangement gives a pleasing appearance as well as better light output.



**Model : KB/TS 240**

### Technical Data

Light Source	: Fluorescent lamp 2 x 18W or 2 x 36W ( 240V 50Hz )
Construction	: In heavy gauge steel sheet and fully pre-treated.
Mechanical Mounting	: Surface mounted.
Dimension	: KB/TS220 2 x 18W = 190mmW x 616mmL x 75mmHt. : KB/TS240 2 x 36W = 190mmW x 1,225mmL x 75mmHt.
Paintwork	: High grade white polyester powder coated high reflectance finish.
Ballast	: 6W extra low loss ballast.
Optional Components	: High frequency electronic ballast. ( EB ) : EL emergency power pack. ( EL ) : 2 amp Fused terminal block. ( FTB ) : Radio interference suppressors. ( RIS )
Applications	: Supermarket and Production line.

### Ordering Code

**Example : KB/TS 140 / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@gmail.com