

Anti Corrosive Fluorescent Fittings

**Model : KCR240 and KCR140****Technical Data**

Light Source	: Fluorescent lamp 18W, 36W or 58W. (240V 50Hz)
Mechanical Mounting	: Surface or wall mounted.
Tightness	: Safety clips. (6nos for 18W, 8nos for 36W and 10nos for 58W)
Ingress Protection	: IP65, with total protection against dust and water jets.
Body	: Made of reinforced polyester with fibreglass. (GRP)
Diffuser	: Prismatic type clear acrylic injected, UV stable with angles studied for total transparency.
Dimension	: KCR120 1 x 18W = 100mmW x 666mmL x 108mmHt. : KCR220 2 x 18W = 170mmW x 666mmL x 108mmHt. : KCR140 1 x 36W = 100mmW x 1,276mmL x 108mmHt. : KCR240 2 x 36W = 170mmW x 1,276mmL x 108mmHt. : KCR158 1 x 58W = 100mmW x 1,576mmL x 108mmHt. : KCR258 2 x 58W = 170mmW x 1,576mmL x 108mmHt.
Reflector	: Steel plating with high grade white polyester powder coated high reflectance finish.
Ballast	: 6W extra low loss ballast.
Optional Components	: High frequency electronic ballast. (EB) : EL emergency power pack. (EL) : 2 amp Fused terminal block. (FTB) : Radio interference suppressors. (RIS)
Applications	: Humid and Dusty areas, Food processing areas and Room with corrosive vapours.

Ordering Code**Example : KCR 240 / EL / FTB / RIS**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun (M) Sdn.Bhd. (128027W) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 (H/L) Fax : 603-80753006 Email : kslite@gmail.com

Q 1
Rev. A