

## Energy Saving System Fluorescent Fittings

Surface mounted or semi-recessed downlight of low installed depth with 2 x PL9W or 1 x 2D 16W compact fluorescent lamp.



**Model : KES800**

### Technical Data

<b>Construction</b>	: Body formed from injection moulded high impact resistance plastic materials with metal base plate.		
<b>Mechanical mounting</b>	: Recessed or surface mounted.		
<b>Light source</b>	: 2 x PL9W ( PL ) : 1 x 2D 16W ( D )		
<b>Dimension</b>	: KES800 / P / PL : KES800 / M12 / PL : KES800 / O / PL                      Width      Length      Height : KES800 / P / D                      240mm      240mm      55mm : KES800 / M12 / D : KES800 / O / D		
<b>Colour</b>	: White.		
<b>Diffuser</b>	: Parabol louvre. ( PL ) : M12 Acrylic. ( M12 ) : Opal moulded. ( O )		
<b>Applications</b>	: Corridor, Car porch, Toilet and Staircase.		

### Ordering Code

**Example : KES/800/P/PL**

Fittings can be supplied in other dimensions if required. All specification and designs shown in this catalogue are subject to change without prior notice.

Manufacturer : Kohsun ( M ) Sdn.Bhd. ( 128027W ) No. 11, Jalan BK1/11, Kinrara Industrial Park, Bandar Kinrara, Puchong 47100 Puchong, Selangor Darul Ehsan, Malaysia. Tel : 603-80751662 ( H/L ) Fax : 603-80753006 Email : kslite@gmail.com

R 1  
Rev. A